



209.00 EUR  
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- INTEL® Cedar Trail-D Processor D2550 + NM10 Chipset
- Support 2 \* DDR3 800/1067MHz Single CH up to 4GB
- Support DirectX 9 Graphics up to 640MHz
- Support 2 \* Serial ATAI (3Gb/s) & 2 \* Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Supports 2 \* Realtek RT8111EVL Gigabit LAN
- 1 \* 24 bits Single Channel LVDS header
- Support Watch dog Technology
- Compliance with ERP standard
- Mini-ITX Form Factor(170mm x 170mm)
- Support Daughter board Expansion
- **CPU**
  - INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz)
- **Chipset**
  - INTEL®NM10 Express chipset
- **Memory**
  - 2 \* DDR3 800/1067MHz Single CH up to 4GB
- **Expansion Slots**
  - 1 \* PCI slot
  - 1 \* Mini PCI-E socket
- **Storage**
  - 2 \* Serial ATAI 3Gb/s + 2 \* Serial ATAIII 6Gb/s connectors
- **Audio**
  - Realtek ALC662 HD Audio Code with 6-Channel

- **Ethernet LAN**
  - **USB**
  - **Special Features**
  - **LVDS**
  - **Rear Panel I / O**
  - **Internal I / O**
  - **BIOS**
  - **Functional**
  - **Packing**
  - **Certificate**
  - **Temperature**
  - **Form Factor**
- 2 \* Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN
  - Embedded 7 \* USB 2.0/1.1
  - Support ACPI S3
  - Support CPU Smart FAN & DC FAN
  - Onboard 24-bits Single Channel LVDS connector
  - 4 \* USB 2.0/1.1 ports
  - 1 \* PS/2 KB/MS connector
  - 2 \* RJ-45 port
  - 1 \* Audio port ( Line-in, MIC and Line-out )
  - 1 \* VGA port
  - 1 \* HDMI port
  - 1 \* COM port
  - 2 \* USB 2.0/1.1 headers for 3 USB 2.0 ports
  - CPU / Chassis Fan connectors
  - 1 \* 24-pin ATX Power connector
  - 1 \* COM header (for RS-232/422/485)
  - 1 \* chassis intrusion header
  - 1 \* 2-pin SPDIF out header
  - 1 \* Parallel header
  - 1 \* GPIO header
  - AMI 16MB DIP-SPI Flash ROM
  - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation, Financial Application
  - Color Box Dimension ■200(W) x 200(D) x 70(H)mm
  - Cases Gross Weight ■15.4KGS
  - Cases Net Weight ■10.3KGS
  - 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm
  - CE, FCC, RoHS
  - Operating within 0~60 centigrade (**Suggest to use system FAN**)
  - Storage within -20-85 centigrade
  - Mini ITX Form Factor(170mmx170mm)

**Product Accessories**

- COM cable
- Manual
- CD
- SATA cable
- I/O shield
- 1x fan