




329.00 EUR

incl. 19% VAT, plus [shipping](#)

- Kabylake !
- 4x LAN !
- 3,5" SBC !

- Intel® Skylake/Kabylake U-series Processor (TDP 15W). Default is 3855U/3955U
- 1 * 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 G
- 3* Intel i225V 2.5GbE, 1* Intel i219LM GbE
- Support Intel AES NI and TPM (option) to secure customers data
- 1 * RS232 Console, 2 * USB3.0 & 3 * USB2.0, 1 * HDMI
- 2* Mini PCIe Slots (1* full size & 1* half size), 1 * SIM card holder
- 12V DC-in power

Model	– JNF731V-3955U (Default) – JNF731V-3965U
Form Factor	– 3.5" (5.8-in * 4.0-in, 148 * 102mm)
Processor System	– Intel® Skylake/Kabylake U-series Processor (TDP 15W) – AMI Flash ROM BIOS
Memory	– 1* DDR4 2133MHz SO-DIMM up to 16GB
Storage	– 1* SATAIII (6 Gb/s) – 1* mSATA (SATA/USB signal)
Expansion	– 1* Full size Mini-PCIe – 1* Half size Mini-PCIe – 1* SIM card holder
Ethernet	– 3* Intel i225V 2.5GbE – 1* Intel i219LM GbE
Graphics	– Intel® HD Graphics, shared memory – 1* HDMI 1.4 (Max Resolution: 4096×2304@24Hz)

Internal I/O	– 3* USB2.0 – 1* SATAIII – 1 * 32GB eMMC (option) (If use Win 10 OS, we recommend the eMMC is use for OS boot up purpose.) – 1* PS/2 – 1* HDMI – 1* RS232/422/485 – 1* Chassis intrusion – 1* GPIO – 1* SMBUS – 1* AT mode – 1* TPM (on board option)
External I/O	Rear: -2* USB3.0 -1* COM -4* RJ45 -12V DC-in
Power	12V DC-in PWR – AT: Directly PWR on as Power input ready – ATX: Press Button to PWR on after Power input ready
Watchdog Timer	– From Super I/O to drag RESETCON# – 256 segments (10sec ~ 255min)
Temperature	– Operating: 0°C ~ 60°C – Storage: -20°C ~ 85°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Compliance	– CE, FCC, RoHS, REACH
OS Support	– Windows, Linux