



5249.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Core i9-14900T !
- ABOX-5220G-i9-RTX2000 !
- NVIDIA RTX™ Embedded 2000 Ada !

- Intel® Core™ i9-14900T 14th Generation / RTX2000 Ada
- 2 x TSN Ready 2.5GbE Controller for Time-Sensitive Network
- 8 x GbE with Optional PoE Support for Easy Connection with IP Camera
- 8 x DI (9~60VDC), 2 x ADC (9~60VDC), and 4 x DO (5V, 100mA)
- Certified with CE, FCC, and E-Mark
- Compliant with EN 50155, EN 45545-2 R25 Standards

For a full PC you need in addition :

- 1x M.2 2280 Key M PCIe 4.0 x4 NVMe SSD
- 1-2x SO-DIMM DDR5-4800 (up to 64Gb)

The PC is completely fanless and is equipped with an Intel Core i9

CPU	Intel® Core™ i9 processor 14900T R680E Chipset
Memory	2 x SO-DIMM Support DDR5-4800 up to 64GB (ECC Support with ECC DRAM)
Watchdog	System power on/off 1 ~ 255 min setting by BIOS
TPM	2.0
Graphics Engine	NVIDIA RTX™ Embedded 2000 Ada
LAN	2 x I226-IT 2.5GbE RJ45 and 8 x I210-AT GbE RJ45 (Optional PoE with Total 120W Power Budget and M12 X-coded Connectors) 4 x RS-232/422/485 Serial Port 8 x USB 3.2 Gen 2x1 10Gbps 8 x DI (9~60VDC), 4 x DO (5V, 100mA) 2 x ADC (9~60VDC)
External I/O Connectors	2 x I226-IT 2.5GbE RJ45 and 8 x I210-AT GbE RJ45 (Optional PoE with Total 120W Power Budget and M12 X-coded Connectors) 2 x HDMI®(Maximum Resolution : 4096 x 2160 @ 60Hz) Additional 2 x HDMI (Maximum Resolution : 4096 x 2160 @ 60Hz) 2 x HDMI®(Maximum Resolution : 4096 x 2160 @ 60Hz) Additional 2 x DP 1.4 (Maximum Resolution : 7680 x 4320 @ 60Hz) 2 x Mini-PCIe
internal I/O	2 x M.2 3042/52 Key B for WWAN (USB3.0) with Dual SIM Support 1 x M.2 2230 Key E for WiFi
Antenna	8 x Pre-cut Hole for External SMA Antenna
Storage	2 x M.2 2280 Key M for PCIe 4.0 x4 NVMe SSD 1 x M.2 2280 Key M for PCIe 4.0 x4 NVMe or SATA SSD (Auto Detection) 2 x 2.5" Drive Bay for SATA Type SSD * RAID 0/1/5 support via Intel® VMD.
Mechanical	Aluminum Alloy Wall-mount
Dimensions	290 x 250 x 98 mm (w/ mounting kit) / 8500g
Operating Temp.	-40°C ~ 70°C w/0.6 m/s airflow (for barebone system)
Storage Temp.	-40°C ~ 80°C - Relative Humidity 10% RH – 90% RH (non-condensing) - Vibration: MIL-STD-810G, Method 514.6, Procedure I, Cat.4 (Operating) IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis
Enviremetal	- Shock: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD (Operating) - Certification: CE, FCC, E-Mark Compliant with EN 50155, EN 45545-2 R25 Standards

	DC 9 – 60V Input (Ignition Management for Variety Vehicle)
	- OCP, OVP, Surge and Reversed Polarity Protection
	- Ignition Detection, and Power on Delay Time Setting by Software
Power	Optional Internal Battery Kit for 10 Mins Operating Time (Charging Temp. 0~45°C, Discharging Temp. -10~60°C)
	* UPS backup time varies depending on actual overall system power consumption and battery is required to be charged before using.
Software	Windows 10 IoT Enterprise LTSC Windows 11 IoT Enterprise LTSC Ubuntu Desktop 22.04