



169.00 EUR  
incl. 19% VAT, plus [shipping](#)

Fully working, recertified mainboard.  
1 year warranty

At just 17cm x 17cm, Mini-ITX is the world's smallest native x86 mainboard platform, and is fully compatible with Microsoft® and Linux Operating Systems.

Now what is this board offering you ?

- 1x DDR266 memory-slot (up to 1024 MB)
- integrated AGP-graphics adapter with MPEG2-decoder (for DVD) (1x VGA-Output , 1x TV-Out(S-Video))
- 1x PCI-Slot (extendable with Riser-Card)
- 2x UltraDMA-133 for drives,1x Floppy-connector
- CPU VIA C3 "Nehemiah" 1,0 GHz with fan
- Connectors : 1xSerial,1xParallel,2xPS/2 (Tastatur,Mouse)
- 4x USB 2.0 connectors
- 2x Firewire
- Sound 1x LineIn,1x Microphon, 1x LineOut and 1x digital(koaxial)
- LAN-Interface 1x RJ-45 (10/100 Mbit)

The VIA C3 processor with 1000 MHz has a fan and is already mounted hard on the board and therefor not changeable  
The 40-mm-fan makes noises at about 2,9 Sone / 38,9 dBA.

The onboard AGP-graphics-adapter uses between 8 and 64 MB of the main-meory as graphic memory.

For proper DVD-Playback, a MPEG2-decoder-chip is installed.

The S/PDIF-Output can be switched into Cinch-TV-Output-mode. The third and fourth USB-ports, both FireWire-ports, and the second serial port are available only with an optional adaptercable.